





Electrically isolated base plate  
Industrial standard package  
Simplified mechanical design, rapid assembly  
Pressure contact

# **Double Diode Module For Phase Control MDx-250-36-C1**

Average forward current	$I_{FAV}$	250 A
Repetitive peak reverse voltage	$V_{RRM}$	3000 ÷ 3600 V
$V_{RRM}$ , V	3000	3200
Voltage code	30	32
$T_j$ , °C	- 40 ÷ 150	



All dimensions in millimeters (inches)

## MAXIMUM ALLOWABLE RATINGS

Symbols and parameters		Units	Values	Test conditions	
<b>ON-STATE</b>					
I <sub>FAV</sub>	Average forward current	A	250 246	T <sub>c</sub> = 98 °C; T <sub>c</sub> = 100 °C; 180° half-sine wave; 50 Hz	
I <sub>FRMS</sub>	RMS forward current	A	393	T <sub>c</sub> = 98 °C; 180° half-sine wave; 50 Hz	
I <sub>FSM</sub>	Surge forward current	kA	5.0 5.8	T <sub>j</sub> =T <sub>j</sub> max T <sub>j</sub> =25 °C	180° half-sine wave; 50 Hz (t <sub>p</sub> =10 ms); single pulse; V <sub>R</sub> =0 V;
			6.0 6.9	T <sub>j</sub> =T <sub>j</sub> max T <sub>j</sub> =25 °C	180° half-sine wave; 60 Hz (t <sub>p</sub> =8.3 ms); single pulse; V <sub>R</sub> =0 V;
I <sup>2</sup> t	Safety factor	A <sup>2</sup> s·10 <sup>3</sup>	125 165	T <sub>j</sub> =T <sub>j</sub> max T <sub>j</sub> =25 °C	180° half-sine wave; 50 Hz (t <sub>p</sub> =10 ms); single pulse; V <sub>R</sub> =0 V;
			145 195	T <sub>j</sub> =T <sub>j</sub> max T <sub>j</sub> =25 °C	180° half-sine wave; 60 Hz (t <sub>p</sub> =8.3 ms); single pulse; V <sub>R</sub> =0 V;
<b>BLOCKING</b>					
V <sub>RRM</sub>	Repetitive peak reverse voltages	V	3000÷3600	T <sub>j min</sub> < T <sub>j</sub> <T <sub>j</sub> max; 180° half-sine wave; 50 Hz;	
V <sub>RSM</sub>	Non-repetitive peak reverse voltages	V	3100÷3700	T <sub>j min</sub> < T <sub>j</sub> <T <sub>j</sub> max; 180° half-sine wave; 50 Hz; single pulse;	
V <sub>R</sub>	Reverse continuous voltages	V	0.75·V <sub>RRM</sub>	T <sub>j</sub> =T <sub>j</sub> max;	
<b>THERMAL</b>					
T <sub>stg</sub>	Storage temperature	°C	- 40 ÷ 50		
T <sub>j</sub>	Operating junction temperature	°C	- 40 ÷ 150		
<b>MECHANICAL</b>					
a	Acceleration under vibration	m/s <sup>2</sup>	50		

## CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions
<b>ON-STATE</b>				
V <sub>FM</sub>	Peak forward voltage, max	V	2.00	T <sub>j</sub> =25 °C; I <sub>FM</sub> =785 A
V <sub>F(TO)</sub>	Forward threshold voltage, max	V	0.90	T <sub>j</sub> =T <sub>j</sub> max;
r <sub>T</sub>	Forward slope resistance, max	mΩ	1.570	0.5 π I <sub>FAV</sub> < I <sub>T</sub> < 1.5 π I <sub>FAV</sub>
<b>BLOCKING</b>				
I <sub>RRM</sub>	Repetitive peak reverse current, max	mA	30	T <sub>j</sub> =T <sub>j</sub> max; V <sub>R</sub> =V <sub>RRM</sub>
<b>THERMAL</b>				
R <sub>thjc</sub>	Thermal resistance, junction to case			180° half-sine wave, 50 Hz
	per module	°C/W	0.0550	
	per arm	°C/W	0.1100	
R <sub>thch</sub>	Thermal resistance, case to heatsink			
	per module	°C/W	0.0200	
	per arm	°C/W	0.0400	

INSULATION						
V <sub>ISOL</sub>	Insulation test voltage	kV	3.00	Sine wave, 50 Hz;	t=1 min	
			3.60	RMS	t=1 sec	
MECHANICAL						
M <sub>1</sub>	Mounting torque (M5) <sup>1)</sup>		Nm	6.00	Tolerance ± 15%	
M <sub>2</sub>	Terminal connection torque (M8) <sup>1)</sup>		Nm	9.00	Tolerance ± 15%	
w	Weight		g	800		

PART NUMBERING GUIDE	NOTES
MD    3    -    250    -    36    -    C1    -    N 1      2      3      4      5      6	<sup>1)</sup> The screws must be lubricated

1. MD - Rectifier Diode  
2. Circuit Schematic  
3. Average Forward Current, A  
4. Voltage Code  
5. Package Type (M.C1)  
6. Ambient Conditions:  
N – Normal

The information contained herein is confidential and protected by Copyright.  
In the interest of product improvement, Proton-Electrotex reserves the right to change data sheet without notice.